

※ Product Parameters

Model	SWC/EST101	SWC/EST101S	SWC/EST111	SWC/EST112	SWC/EST112S	SWC/EST114
Product Type	Standard electric strike		Short panel electric strike	American standard electric strike (short panel)		Long panel electric strike
Product Image						
Lock Size	150x40x28(mm)	150x40x34(mm)	160x25x28(mm)	124x32x33(mm)		250x25x28(mm)
Holding Stength	500KG					
Lock structure	Stainless Steel					
Input Voltage	DC12V±10%					
Working Current	200mA	200mA	200mA	320mA	320mA	200mA
Suitable Temperature	-10~+55℃ (14-131F)					
Door Type Applicable	Wooden Door, Metal Door, PVC Door					
Signal Output	No	Yes	No	No	Yes	No
Security Type	Lock When Power off(Standard), Unlock When Power off(Customizable)					
Weight	0.3KG	0.4KG	0.4KG	0.34KG	0.35KG	0.4KG

Model	SWC/EST113	SWC/EST113S	SWC/EST115	SWC/ESTNW116	SWC/EST117	SWC/ESTGL118
Product Type	American Standard Electric Strike (Long Panel)		Long Type European Electric Strike	European Narrow-type and Adjustable Electric Strike	Adjustable Electric Strike With Narrow Frame	Glass Electric Strike
Product Image						
Lock Size	165x32x33(mm)		250x32x33(mm)	250x25x32(mm)	110x25x32(mm)	160x25x31(mm)
Holding Stength	500KG					
Lock structure	Stainless Steel					
Input Voltage	DC12V±10%					
Working Current	200mA	200mA	200mA	200mA	200mA	200mA
Suitable Temperature	-10℃ ~+55℃ (14-131F)					
Door Type Applicable	Wooden Door, Metal Door, PVC Door					
Signal Output	No	Yes	No	Yes	Yes	No
Security Type	Lock When Power off(Standard), Unlock When Power off(Customizable)					
Weight	0.4KG	0.4KG	0.42KG	0.4KG	0.28KG	0.4KG

* Weight and Size are Only Approximation and May be Modified Without Prior Notification.



www.smartworld.ae

Note: Please carefully read User Manual before usage
For detailed specification and functions, please refer to User Manual; in case of inconsistency, the content in User Manual should be kept.